

B. C. LAND INVENTORY (C. L. I.)



FULTON RIVER

CODE LEGEND

ANN PPT - ANNUAL PRECIPITATION (INCHES)
 MAY-SEPT PPT - MAY-SEPT RAINFALL (INCHES)
 NOV-MAR SNOWFL - NOVEMBER-MARCH SNOWFALL (INCHES)
 MAX SNOWPK - NORMAL MAXIMUM SNOWPACK (INCHES)
 FSR - FREQUENCY OF SUMMER RAIN > 0.6" (DAYS)
 FWS - FREQUENCY OF WINTER SNOW > 2.0" (DAYS)
 HDD - HEATING DEGREE DAYS (< 32°F THRESHOLD)
 TDD - THAWING DEGREE DAYS (> 32°F THRESHOLD)
 FDD - FREEZING DEGREE DAYS (< 32°F THRESHOLD)
 FFP - FROST FREE PERIODS (DAYS)
 PET - POTENTIAL EVAPOTRANSPIRATION (INCHES)
 E0 - EVAPORATION FROM OPEN WATER (INCHES)
 CCA - CLIMATE CAPACITY FOR AGRICULTURE
 APP - AIR POLLUTION POTENTIAL

GDD - GROWING DEGREE DAYS (74°F THRESHOLD)

Scale 1:125,000 Échelle



DOUBLE ENTRY INDICATES A RANGE WITHIN THE UNIT
 THE FIRST VALUE OF DOUBLE ENTRY REPRESENTS THE LOWER PORTION OF UNIT
 + IS READ AS GREATER THAN
 - IS READ AS LESS THAN
 IN GDD, FFP, CCA AND APP VALUES WITHIN DOUBLE ENTRIES ARE LISTED IN DECREASING ORDER OF ABUNDANCE.

CLIMATE DATA MAP - PROVISIONAL

93L/NE

JAN 11/74

93L/NE

UNIT	ANN. PPT. (IN)	MAY-SEPT PPT. (IN)	NOV-MAR SNOWFL. (IN)	MAX. SNOWPK. (IN)	F.S.R. (DAYS)	F.W.S. (DAYS)	HDD/10°	TDD/10°	FDD/10°	GDD	FFP	P.E.T.	E ₀	CCA	APP	UNIT
1	18	7.0	60	20-	2	2-	10.6	36.6	39.0	1750	55	18.0	23.4	4F	S	1
2	18	7.0	60	20	2	2-	9.4	36.6	39.0	1800	75	18.0	23.4	3G	MS	2
3	18	7.0	60	20	2	2-	10.3	37.2	38.0	1750	55	18.0	23.4	4F	M	3
4	18	7.0	60	20	2	2-	10.6	36.6	39.0	1800	75	18.0	23.4	3G	M	4
5	18	7.0	60	20	2	2-	10.6	36.6	39.0	1800	75	18.0	23.4	3G	SM	5
6	20	9.0	60	20	2	2-	9.4	39.1	34.6	1400	40	17.0	22.1	5FG	M	6
7	20	9.0	60	20	2	2	9.6	36.6	35.4	1400	40	16.0	20.8	5FG	L	7
8	25	12.0	80	40	5	5	10.5	36.9	38.4	1000	30-	15.0	20.8	6H	L	8
9	35	15.0	150+	60	10	10	13.0	31.6	48.0	1000	30-	16.0	20.8	6H	L	9
10	30	12.0	150+	40	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	10
11	18	7.0	60	20	2	2	9.3	39.5	34.2	1400	40	17.0	22.1	5FG	ML	11
12	25	12.0	150	60	5	5	10.6	36.6	39.0	1750	70	19.0	24.7	3G		12
13	25	12.0	150	60	5	5	15.6	27.4	25.6	1400	40	17.0	22.1	5FG	L	13
14	25	9.0	80	40	2	2	11.0	36.4	16.5	1000	30-	16.0	20.8	6H	L	14
15	30	12.0	150	60	5	5	15.6	27.4	25.6	1400	40	17.0	22.1	5FG	L	15
16	30	12.0	150	60	5	5	15.6	27.4	25.6	1400	40	17.0	22.1	5FG	L	16
17	30	12.0	150	60	5	5	15.6	27.4	25.6	1400	40	17.0	22.1	5FG	L	17
18	40+	15.0+	300+	80+	10+	10+	17.2+	23.6+	30.4+	800+	30-	15.0+	19.5+	7H	L	18
19	40+	15.0+	300+	80+	10+	10+	17.0+	24.0+	30.0+	800+	30-	15.0+	19.5+	7H	L	19
20	25	9.0	80	40	2	2	9.6	36.6	35.4	1000	30	17.0	22.1	6H	L	20
21	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	21
22	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	22
23	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	23
24	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	24
25	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	25
26	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	26
27	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	27
28	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	28
29	30	15.0	150+	80+	10+	10+	14.8+	28.2+	52.0+	800+	30-	15.0+	19.5+	7H	L	29
30	35	15.0+	150+	80	10+	10+	14.8+	28.2+	52.0+	800+	30-	15.0+	19.5+	7H	L	30
31	25	9.0	120	40-	2	2	9.6	36.6	35.4	1400	40	18.0	23.4	5FG	L	31
32	25	12.0	150	60	5	5	13.7	26.2	27.5	1000	30-	15.0	19.5	6H	L	32
33	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	33
34	25	9.0	80	20	2	2	11.0	31.8	21.9	1400	40	17.0	22.1	5FG	SM	34
35	25	12.0	150	60	5	5	13.7	26.2	27.5	1000	30-	15.0	19.5	6H	L	35
36	25	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	36
37	25	12.0	150	60	5	5	13.7	26.2	27.5	1000	30-	15.0	19.5	6H	L	37
38	25	9.0	150	20	2	2	10.7	32.4	21.1	1000	30-	18.0	23.4	6H	L	38
39	30	12.0	150	60	5	5	12.0	33.8	44.0	1000	30-	16.0	20.8	6H	L	39
40	35+	15.0+	150	80	10+	10+	14.8+	28.2+	52.0+	800+	30-	15.0+	19.5+	7H	L	40
41	20	9.0	80	20	2	2-	10.3	37.2	38.0	1400	40	17.0	22.1	5FG	SM	41