Wave action and related erosion at high lake levels may present a special flood hazard depending on site specific conditions. SKAHA LAKE FLOOD LEVEL 339.2 metres G.S.C. Datum **Use and Limitations of Floodplain Maps** Users must note the dates of base mapping, aerial photography, river surveys and issue of mapping relevant to dates of development in the map area. Subsequent developments or changes within the floodplain or channel (natural or constructed) will affect flood levels and render site-specific map Floodplain maps are administrative tools which depict minimum flood elevations and floodplain boundaries. Flooding may occur outside of the designated floodplain boundary. Floodplain maps do not provide information on site-specific flood hazards such as, land erosion or high water velocity, sudden shifts in the channel of the watercourse, or alluvial and debris flow fan areas. Other sources of water, roads, railways or other barriers can restrict water flow and affect local flood levels. As well, obstructions such as ice and debris, flooding in surrounding areas, channel deposition, groundwater or other phenomena can cause flood levels to exceed those indicated on the map. Land adjacent to a floodplain may be subject to flooding from tributary watercourses. PENTICTON AIRPORT Floodplain maps do not indicate or locate legal survey boundaries. A site survey is required to reconcile property location, ground elevations, and designated flood level information. The accuracy of the location of a floodplain boundary as shown on this map is limited by the base topography. It is generally assumed to be plus or minus one-half the increment of the ground contours. Professional assistance and detailed engineering analysis are required to address any of the above S The floodplain limits as shown are within the accuracy of the base mapping. Site specific ground elevations should be confirmed by field survey. CANADA BRITISH COLUMBIA FLOODPLAIN MAPPING AGREEMENT KEY MAP REVISIONS FLOODPLAIN DATA LEGEND NOTES

ELLIS CREEK

FAN - SEE NOTE

SHEET 14.

310-0000 ENVIRONNEMENT CANADA . COLOMBIE-BRITANNIQUE MINISTÈRE EAUX INTÈRIEURES DE L'ENVIRONNEMENT Produced by: British Columbia Water Management Branch, Special Projects Section, Floodplain Mapping Program. 1. The floodplain areas as depicted on this map have been interim designated pursuant to the Canada/British Columbia Floodplain Mapping Agreement (1988) by the Minister of the Environment for Canada and the Minister of Environment, Lands and Parks for British Columbia. L'ACCORD CANADA COLOMBIE-BRITANNIQUE SI LA CARTOGRAPHIE DES PLAINES D'INONDATIO DESCRIPTION DESIGNATED Flooding may still occur outside of the interim designated floodplain areas. The Ministers do not assume any liability by reason of the interim designation or failure to interim designate areas on this map. 82E FLOODPLAIN River survey done by Surveys Section, Water Management Branch, Project 79-OBIP-2, 1979 and 1980. a) Horizontal control based on provincial FLOODPLAIN MAPPING DRAWN LIMIT T. C. E. . The Designated Flood has a statistical frequency of occurrence of once every 200 years. SCALE a) Horizontal control based on provincial network.
b) Elevations are in metres and are referred to Geodetic Survey of Canada datum. (indicates Survey Monument.)
Reference Map Series 1:20 000,
Surveyor General Branch, 1992.
Base mapping done by Map Production
Division, Surveys and Resource Mapping
Branch, Project 79-126T-0, NAD 27.
Airphotography date: June 1975
a) Contour interval 1 metre and greater; spot elevatons shown to 0.1 metres, with accuracy to ± 0.3 metres, except where noted.
b) Grid origin referred to U.T.M.
Projection Zone 10. 3. The flood levels were computed using a standard step method modelling technique, assuming open water flow conditions. 1:5 000 OKANAGAN RIVER CHECKED _ FLOOD LEVEL 4. The floodplain limits assume the absence of all dykes. NEGATIVE No. 5. The floodplain limits and flood levels include an allowance for freeboard. RIVER RIVER SURVEY B. R. S. OSOYOOS TO PENTICTON Mapping: 6. The floodplain limits are not established on the ground by legal survey. 200 Year Frequency 7. The floodplain limits are not delineated for side streams and tributaries. DRAWING No. REV. 8. The required setback of buildings from the natural boundaries of lakes and watercourses to allow for the passage of floodwaters and possible bank erosion is not shown. This information is available either through local municipalities or the Ministry of Environment, Lands and Parks. DESIGNED B. B. Scale in metres 89-12-13 9. MAPS AVAILABLE FROM MAPS B.C., MAP AND AIR PHOTO SALES, VICTORIA, B.C. APPROVED TOO AL ENGINEER RW Miche SHEET 13 of 15 RECOMMENDED (METRES G.S.C. DATUM) SCALE 1:500 000 10. For detailed description of Water Resources Service reference monuments, see drawing A-5221-INDEX and drawing A-5221-1 to -19

DDflmg