


NOTE: Mapping incomplete at this time.



Use and Limitations of Floodplain Maps

- Users must note the dates of base mapping, aerial photography, river surveys and issue of mapping relevant to dates of development in the map area. Subsequent developments or changes within the floodplain or channel (natural or constructed) will affect flood levels and render site-specific map information obsolete.
- Floodplain maps are administrative tools which depict minimum flood elevations and floodplain boundaries. Flooding may occur outside of the designated floodplain boundary.
- Floodplain maps do not provide information on site-specific flood hazards such as, land erosion or high water velocity, sudden shifts in the channel of the watercourse, or alluvial and debris flow fan areas.
- Other sources of water, roads, railways or other barriers can restrict water flow and affect local flood levels. As well, obstructions such as ice and debris, flooding in surrounding areas, channel deposition, groundwater or other phenomena can cause flood levels to exceed those indicated on the map. Land adjacent to a floodplain may be subject to flooding from tributary watercourses.
- Floodplain maps do not indicate or locate legal survey boundaries. A site survey is required to reconcile property location, ground elevations, and designated flood level information.
- The accuracy of the location of a floodplain boundary as shown on this map is limited by the base topography. It is generally assumed to be plus or minus one-half the increment of the ground contours.
- Professional assistance and detailed engineering analysis are required to address any of the above considerations.

NOTES

Produced by: British Columbia Environmental and Engineering Service
Floodplain Mapping Program

Survey: River survey done by Surveys Section,
Water Management Branch.
a) Horizontal control based on provincial network.
b) Elevations are in metres and are referred to Geodetic Survey of Canada datum. L indicates Survey Monument 1.

Mapping: Mapping done by Map Production Division, Surveys and Mapping Branch.
a) Contour interval - 1 metre and greater; Spot elevations shown to 0.1 metres, with accuracy to ± 0.3 metres.
b) Grid origin referred to U.T.M. Projection, Zone II (1975).

FLOODPLAIN DATA

- a) Flood profiles were computed by a standard step method modelling technique.
b) Floodplain limits assume absence of all dykes.
c) Floodplain limits and flood levels include allowance for freeboard.
d) Position of floodplain boundary not established on ground by legal survey.
e) See "Flood Control Requirements" for minimum distances allowed from buildings to natural boundaries of watercourses and lakes.
f) Floodplain limits are not delineated for side streams or tributaries.

* Correspondence to Municipalities, Oct. 30, 1973.

LEGEND


200 Year
Floodplain Limit

Flood levels in metres
above G.S.C. Datum

352.7 200 Year Frequency
352.3 20 Year Frequency

Flood Level
Contour
(Levels include 0.6 m. freeboard)

KEY MAP



REVISIONS

No.	DESCRIPTION	DATE
1	CROSS SECTION LOCATIONS AND SURVEY MONUMENTS ADDED	SEPT. 1986

ORTHOPHOTO
MAPPING
Date of Photography
Oct. 1974, Sept. 1975 & 1976

MAPPING
INFORMATION
Checked: J.B.

FLOODPLAIN
INFORMATION
Checked: C.W.D.


ISSUE OF MAPPING
Date: June, 1980



Province of
British Columbia

Ministry of the Environment
ENVIRONMENTAL AND ENGINEERING SERVICE
WATER INVESTIGATIONS BRANCH

FLOODPLAIN MAPPING SHUSWAP RIVER Mara Lake To Mabel Lake



RECOMMENDED
DIVISION CHIEF

APPROVED
DEPUTY MINISTER

FILE No.

0305030-8

SCALE

1:5000

DWG. No.

A5241-10

SHEET

10 OF 17

D D