

Use and Limitations of Floodplain Maps

- Floods result from the rates of land drainage, terrain and geography, river surveys and levels of recurring storms or floods as experienced to the date of the study. Subsequent developments or changes which the floodplains or channel features or characteristics will affect flood levels and render the maps and information obsolete.
- Floodplain maps are administrative tools which depict minimum flood elevations and floodplain boundaries. Flooding may occur inside or outside designated floodplain boundaries.
- Floodplain maps do not provide information on site-specific flood hazards such as, land erosion or high water velocity, sudden shifts in the channel of the watercourse, or alluvial and debris flow fan areas.
- Other sources of water, roads, railways or other barriers can restrict water flow and affect local flood levels. As well, obstructions such as ice and debris, flooding of tributary streams, channel deposition, groundwater or other phenomena can cause flood levels to exceed those indicated on the map. Land adjacent to a floodplain may be subject to hazards from tributary watercourses.
- Floodplain maps do not indicate or involve legal survey boundaries. A site survey is required to reconcile property boundaries, ground elevations, and designated flood level information.
- The accuracy of the location of a floodplain boundary as shown in this map is limited by the basic topography. It is generally assumed to be plus or minus one-half the increment on the contour interval.
- Professional assistance and detailed engineering analysis are required to address any of the above considerations.

MAPPING

BRITISH COLUMBIA WATER RESOURCES SERVICE FLOODPLAIN MAPPING PROGRAM

Field surveys and map production done by Planning & Surveys Division, Water Investigations Branch, Water Resources Service. Photogrammetric Mapping done by Map Production Division, Surveys & Mapping Branch, Lands Service.

1) SURVEYS
   (a) Horizontal Control based on Provincial Network
   (b) Vertical Control based on Geodetic Survey of Canada (1968)
2) MAPPING
   (a) Contour interval 1 metre and greater. Spot elevations shown to 0.1 metres with accuracy + 0.15 metres.
   (b) Grid origin referred to UTM Projection Zone 10
   (c) Cadastral detail approximate only and based on best local information.

FLOODPLAIN LIMITS


a) Flood profiles were computed by a standard step method modelling technique.
b) Floodplain Limits shown assume absence of all dykes.
c) Floodplain Limits and Flood Levels include 2 ft. (0.61 m) allowance for freeboard.
d) Position of floodplain boundary not established on ground by legal survey.
e) See "Flood Control Requirements" * for minimum distance allowed from building to natural boundaries of water courses and lakes.
f) Floodplain Limits are not delineated for side streams or tributaries.

* Correspondence to Municipalities October 30, 1973.

LEGEND

- 200 Year Frequency Floodplain Limit
- 20 Year Frequency Floodplain Limit
- 351.2 Flood Level 200 Year Frequency Flood in Metres
- 349.6 Flood Level 20 Year Frequency Flood in Metres

KEY MAP



ZONE 10
SCALE 1:250,000

REVISIONS

NO	DESCRIPTION	DATE

ORTHOPHOTO MAPPING
DATE OF PHOTOGRAPHY OCT. 14, 1974

MAPPING INFORMATION
CHECKED

FLOOD PLAIN INFORMATION
CHECKED

ISSUE OF MAPPING
DATE JUNE, 1976

BRITISH COLUMBIA
DEPARTMENT OF ENVIRONMENT
WATER RESOURCES SERVICE
WATER INVESTIGATIONS BRANCH

KAMLOOPS AREA
FLOOD PLAIN MAPPING
THOMPSON AND NORTH THOMPSON RIVERS

SCALE IN METRES 50 0 50 100 150 200 250

RECOMMENDED DIVISION CHIEF

APPROVED DEPUTY MINISTER

FILE NUMBER 0310213-4

SCALE 1:2500

DWG NO 5112

SHEET 8 OF 19